



Accelerator Studies in China

Qing QIN for the accelerator team in IHEP

Institute of High Energy Physics, CAS

Outlines



- Introduction
- Plan on CEPC + SppC
- Hadron machine in China
- Key technology for SppC
- Summary

Large science facilities




IHEP serves as the backbone of China's large science facilities

- **In operation**
 - Beijing Electron Positron Collider (BEPCII)
 - Beijing Spectrometer (BESIII)
 - Beijing Synchrotron Radiation Facility (BSRF)
 - Yangbajing Cosmic Ray Observatory: ASg & ARGO
 - Daya Bay Neutrino Experiment
- **Under construction**
 - China Spallation Neutron Source (CSNS)
 - Hard X-ray Modulation Telescope(HXMT)
 - Accelerator-driven Sub-critical System (ADS)
 - Jiangmen Neutrino Underground Observatory (JUNO)
- **Under planning**
 - HEPS, LHAASO, XTP, HERD, ...

Large science facilities




BEPC



Daya Bay



CSNS



C-ADS



Yangbajing Cosmic Ray observatory




中国科学院 **HEPS** 高能物理研究所
Institute of High Energy Physics

08-26-14

Next

Hadron colliders

BEPC & BEPCII




Beijing Electron Positron Collider (BEPC)
— 1st HEP accelerator in China


From BEPC to BEPCII



- BEPCII (Upgrade project of BEPC)
 - a double-ring factory-like machine
 - deliver beams to both HEP & SR



Accelerator —3-ring structure



08-26-14

Next steps in the Energy Frontier -
Hadron Colliders

中国科学院高能物理研究所
Institute of High Energy Physics

Design Goals of BEPCII



□ Collision Mode

- Beam energy range **1-2.1 GeV**
- Optimized beam energy **1.89 GeV**
- Luminosity **$1 \times 10^{33} \text{ cm}^{-2}\text{s}^{-1}$ @1.89 GeV**
- Full energy injection **1-1.89 GeV (2.3/2.5 GeV, e⁺/e⁻)**

□ SR Mode

- Beam energy **2.5 GeV (full energy injection)**
- Beam current **250 mA**
- Keep the present beam lines useable


**Features: One machine, two purposes (HEP, SR),
small circumference, big operation energy range**

Peak luminosity at different beam energy

Beam energy	Peak luminosity	Max. beam-beam parameter
1.89 GeV	7.08 E32 /cm ² /s	0.035, 0.042@70mA
1.55 GeV	2.92 E32 /cm ² /s	0.028
1.84 GeV	5.07 E32 /cm ² /s	0.031
2.01 GeV	6.50 E32 /cm ² /s	0.032
2.13 GeV	6.28 E32 /cm ² /s	0.038, 0.04@450mA
2.18 GeV	5.37 E32/cm ² /s	0.037
2.3 GeV	3.0 E32/cm ² /s	0.023




Luminosity evolution at the design energy



2. Plan on CEPC + SppC



- BEPC to BEPCII, and then to **where** in the future?



CEPC+SppC


CEPC: $E_{cm}=240\text{GeV}$ e⁺e⁻ Circular Collider
 SppC: $E_{cm}=50\text{-}100\text{TeV}$ pp Collider

**HIEPAF: High Intensity
 Electron Positron
 Accelerator Facility**

Evolution of BEPC




- CEPC – Circular e^-/e^+ Collider as a Higgs Factory
- SppC – Super pp Collider in the same tunnel



- CEPC contains a linac, a booster, and a ring.

Main parameters of CEPC

- e beam energy
- ✓ $E_b = 120 - 125$ GeV
- ✓ Beamstrahlung limits luminosity near 125 GeV
- ✓ $E_b = 120$ GeV is chosen.
Cross-section = 200 fb




- The circumference is determined by that of the SppC.
- ✓ dipole field $B = 20$ T proton beam energy
- ✓ 2 schemes are considered: $C = \sim 50$ km & ~ 70 km
 $C = 50$ km (minimum size)

Accelerator Baseline



- LINAC** to generate and accelerate electrons to 6 GeV
- Booster** to accelerate electrons to 120 GeV
- Main Ring** to accumulate electrons to 16.9 mA, FODO lattice, single ring with the Pretzel scheme ...



Main parameters of CEPC ring



Parameter	Unit	Value	Parameter	Unit	Value
Energy	GeV	120	Circumference	km	53.6
Number of IP		2	SR loss	(GeV/turn)	3.01
N_e /bunch	1E11	3.71	N_b /beam		50
Beam current	mA	16.6	SR power/beam	MW	50
Partition J_e		2	Long. damp. time	ms	6.7
Dipole field	Tesla	0.0658	Bending radius	km	6.094
Emittance (x/y)	nm	6.8/0.0204	β_{IP} (x/y)	mm	800/1.2
Trans. size (x/y)	μm	73.70/0.16	Mom. compaction	1E-4	0.415
$\xi_{x,y}$ /IP		0.104/0.074	Bunch length	mm	2.26
RF voltage V_{rf}	GV	6.87	RF frequency f_{rf}	GHz	0.7
Long. Tune ν_s		0.206	Harmonic number		125208
Hourglass factor		0.687	Energy acceptance	%	2
Lifetime (simu.)	hr	1.5	L/IP (10^{34})	$\text{cm}^{-2}\text{s}^{-1}$	1.82


08-26-14

A pre-CDR will be done before the end of 2014.





Critical Parameters



- **Circumference: 53.6 km**
- **SR power: 50 MW/beam**
- **16 arcs**
- **2 IPs**
- **8 RF cavity sections (distributed)**
- **6 straight sections (for injection and beam dump)**
- **Filling factor of the ring: ~80%**



Lattice design for CEPC ring



物理研究所
Energy Physics

08-26-14 $\delta_E / p_{0c} = 0.$

Next steps in the Energy Frontier -
Hadron Colliders


[*10** (3)]

Beam-beam study for CEPC

Weak strong simulation





- Self consistent bunch length for beamstrahlung



Instability study for CEPC



- RF cavities (Number = 378)



- Impedance and wake

Object	Contributions			
	R [kΩ]	L [nH]	k_{loss} [V/pC]	$ Z_{//}/n _{\text{eff}}$ [Ω]
Resistive wall (Al)	16.8	214.4	552.1	0.0075
RF cavities	40.1	---	1313.6	---
Total	56.9	214.4	1865.7	0.0075

$$W(s) = -Rc\lambda(s) - Lc^2\lambda'(s)$$


Next steps in the Energy Frontier -
 Hadron Colliders

RF cavity design study




Cavity type

➤ High loss cavity or low loss cavity?



Low loss cavity



High loss cavity

	Low loss	High loss
$f(\text{MHz})$	704	704
$R_{\text{iris}}(\text{mm})$	55	55
$R/Q(\Omega)$	625.783	579.438
$G(\Omega)$	276.768	251.371
$k_l(\text{V/pC})$	2.965	1.873



$$\frac{P_{c-low}}{P_{c-high}} = \frac{(R/Q)_{high}}{(R/Q)_{low}} = 92.6\%$$

$$\frac{P_{HOM-low}}{P_{HOM-high}} = \frac{k_{l-low}}{k_{l-high}} = 158.3\%$$

For beam current 5.05mA:

$$P_{HOM-low} / \text{cavity} = 2.694 \text{ kW}$$

$$P_{HOM-high} / \text{cavity} = 1.702 \text{ kW}$$

➔ **High loss cavity better!**

From CEPC to SppC



- Use the same CEPC tunnel to build SppC, exploring new physics beyond SM
 - Maximize the beam energy to 70-100 TeV range by using 20 T SC magnets
 - Keep the e-/e+ rings when add the SppC
 - Possible collisions: pp, e-/e+, ep, pA, eA, AA
 - Build a new injector chain for SppC (proton and ions)
 - Independent physics programs for the accelerators of the injector chain
-

Accelerator Baseline Design



• Proton-proton collider luminosity


$$L_0 = \frac{N_p^2 N_b f_{rep} \gamma}{4\pi \epsilon_n \beta_{IP}} F \quad \left(F = \sqrt{1 + \left(\frac{\theta_c \sigma_z}{2\sigma_{x,IP}} \right)^2} \right) \quad \xi = \frac{N_p r_p}{4\pi \epsilon_n} \leq 0.004$$

• Main constraint: high-field superconducting dipole magnets

- 50 km: $B_{\max} = 12 \text{ T}, E = 50 \text{ TeV}$
- 50 km: $B_{\max} = 20 \text{ T}, E = 70 \text{ TeV}$
- 70 km: $B_{\max} = 20 \text{ T}, E = 90 \text{ TeV}$

$$B_{\min} = \frac{2\pi(B\rho)}{C_0}$$

Basic Machine Parameters (in progress)




SppC Machine Parameters	Option 1	Option 2
Beam energy [TeV]	25	45
Circumference [km]	50	70
SR loss/turn [keV]	440	4090
Bunch population	1.3×10^{11}	0.98×10^{11}
Bunch numbers	3000	6000
Beam current [mA]	0.5	0.405
SR power/beam (MW)	0.22	1.66
B_0 [T]	12	19.24
Bending radius [km]	6.9	7.8
Momentum compaction factor	3.5×10^{-4}	2.5×10^{-4}
β_{IP} x/y (m)	0.1/0.1	0.1/0.1
Emittance ($\mu\text{m}\cdot\text{rad}$)	4	3
ξ_y/IP	0.004	0.004
Luminosity/IP ($\text{cm}^{-2}\text{s}^{-1}$)	2.15×10^{35}	2.85×10^{35}

Main features on accelerator physics



- **Very high luminosity: $\sim 3 \times 10^{35} \text{ cm}^{-2}\text{s}^{-1}$**
 - Supported by powerful injector chain and strong focusing at lps
 - Integrated luminosity enhancement by exploring emittance damping (synchrotron radiation)
- **Very high synchrotron radiation power: 56 W/m**
 - High circulation current: 1 A (similar to HL-LHC)
- **Machine protection by sophisticated collimation system (6.3 GJ per beam; inefficiency: 10^{-7})**
- **Instability issues**
 - Electron cloud, resistive wall (beam screen) etc.
- **Challenges in lattice design**
 - Insertion lattice (IP, injection, extraction, collimation)
 - Compatible with the existing CEPC rings


3. Hadron machine in China




• China Spallation Neutron Source (CSNS)

Beam power (kW)	Repetition rate (Hz)	Beam current (mA)	Energy (GeV)	neutron flux (n/cm ² /s)
100	25	63	1.6	2×10 ⁷


Project Phase	I	II
Beam Power on target [kW]	100	500
Proton energy [GeV]	1.6	1.6
Average beam current [μ A]	62.5	312.5
Pulse repetition rate [Hz]	25	25
Linac energy [MeV]	80	250
Linac type	DTL	+Spoke
Linac RF frequency [MHz]	324	324
Macropulse. ave current [mA]	15	40
Macropulse duty factor	1.0	1.7
RCS circumference [m]	228	228
RCS harmonic number	2	2
RCS Acceptance [mm-mrad]	540	540
Target Material	Tungsten	Tungsten



Power Map of Proton Accelerators



Milestones of CSNS



Feb. 2001	idea of CSNS discussed
June 2005	proposal approved in principle by central government
Jan. 2006	CAS funded 30M CNY for R&D I
July 2007	Guangdong funded 40M CNY for R&D II
Dec. 2007	proposal reviewed
Sept. 2008	proposal approved by government
Oct. 2009	feasibility study reviewed
Apr. 2010	site preparation start
Feb. 2011	feasibility study approved
May 2011	preliminary design approved
Sept. 2011	construction started

Site



- CSNS is the first large science facility in southern part of China. It can balance the present uneven distribution of the facility, and promote advanced researches in the economic developed zone of Guangdong-Hong Kong.
- The Dongguan local government provided a land of about **0.67 km²** for CSNS facility. **0.27 km²** is planned for the phase-I construction.

Site Preparation & Construction



中国散裂中子源装置地A点拍摄 (09.5.9)

May 2009



中国散裂中子源工程进展照片 (2014.6)

August 2014

08-26-14

Next steps in the Energy Frontier
Hadron Colliders

for
ics




Ion source




RFQ & power source




DTL & klystron



Quad




Quad in RCS



RCS


RTBT



RCS RF cavity



Ext. kicker



Stripper foil



Collimator



RCS dipole



PS for main magnet



08-26-14
RCS RF power source

Next steps in the Energy Frontier
Hadron Colliders

研究所
physics



RFQ & its conditioning



RCS RF cavity & conditioning



08-26-14

RCS dipole in mass production



Next steps in the Energy Frontier
Hadron Colliders



Pulsed PS for LINAC

Physics





-
- **Chinese Accelerator Driven Subcritical System (C-ADS)**
 - Nuclear waste is a **bottleneck** for nuclear power development in China.
 - ADS has been recognized as a **good option** for nuclear waste transmutation, but never established for test in the world , many challenges faced.
 - As a long-term program, ADS R&D has been **supported by CAS**.

Principle of ADS



Roadmap of ADS Project in China




“Strategic Priority Research Program”
of the Chinese Academy of Sciences

Layout of Accelerator




- The proton accelerator is being built by IHEP and IMP together.
- This project has begun from early 2011.




1) RFQ of Injector I

4 technical modules, **64** tuners, **4** RF power couplers, **4** dipole rods on each plate .



The beam transmission is about 98.7%

Parameters	Value
Frequency (MHz)	325
Injection energy (keV)	35
Output energy (MeV)	3.2128
Pulsed beam current (mA)	15
Beam duty factor	100%
Inter-vane voltage V (kV)	55
Beam transmission	98.7%
Average bore radius r_0 (mm)	2.775
Vane tip curvature (mm)	2.775
Maximum surface field (MV/m)	28.88 (1.62Kilp.)
Input norm. rms emittance (x,y,z)(π mm.mrad)	0.2/0.2/0
Output norm. rms emittance(x/y/z) (πmm.mrad/MeV-deg)	0.2/0.2/0.0612
Vane length (cm)	467.75
Accelerator length (cm)	469.95



No. 12,3 4 module of RFQ on site


08-26-14

Next steps in the Energy Frontier -
Hadron Colliders


2) Spoke012 Cavity ($\beta=0.12$) of Injector I




Main Geometrical parameters	Units	Value
Diameter of cavity	mm	468
Length of cavity	mm	180
Diameter of beam tube	mm	35
RF parameters	Units	Value
$E_{\text{peak}}/E_{\text{acc}}$		4.54
$B_{\text{peak}}/E_{\text{acc}}$	mT/(MV/m)	6.37
G	Ω	61
Transition Time Factor		0.76
$R/Q@\beta=0.12$	Ω	142



The Convex end wall (right) is adopted, which has better mechanical performance than the flat one (left).





E-field



B-field

Note: Effective length for E_{acc} is defined as $\beta\lambda$

Fabrication of Spoke012 cavity finished on Nov. 8, 2012





08-26-14

Next steps in the Energy Frontier -
Hadron Colliders

中国科学院高能物理研究所
Institute of High Energy Physics


Vertical test of Spoke012 cavity



✓ $Q_0 = 5.8 \times 10^8$ @ 6 MV/m, 4K;

✓ $Q_0 = 3.4 \times 10^8$ @ 7 MV/m, 4K

Horizontal test result on Sept. 12, 2013 — the first horizontal test for the low beta proton SC cavity



✓ $Q_0 = 2.2 \times 10^8$ @ 6.5 MV/m, 4K;
 ✓ $Q_0 = 8.5 \times 10^8$ @ 5 MV/m, 4K
 ✓ Fit the requirement of ADS.

08-26-14

Next steps in the
Hadron Colliders

Spoke021 cavity



650MHz (preparing for test)







08-26-14

Next steps in the Energy Frontier -
Hadron Colliders

中国科学院高能物理研究所
Institute of High Energy Physics

3) HWRs for Injector II




08-26-14

Next steps in the Energy Frontier -
Hadron Colliders


高能物理研究所
Institute of High Energy Physics

VT results of HWR




Horizontal Test of HWR


Op. Temperature	4.4 K
Op. Pressure	1.25 bar
Cooling	bath
Pressure	± 1.5 mbar
Dynamic load	10 W
Solenoid storage	27KJ



Next steps in the Energy Frontier -
Hadron Colliders



Solid State Amplifier



162.5 MHz / 40 kW



162.5 MHz / 20 kW

The solid state amplifiers of 162.5 MHz at 20 kW and 40 kW were tested. All requirements for specifications are reached.

08-26-14

Next steps in the Energy Frontier -
Hadron Colliders

中国科学院高能物理研究所
Institute of High Energy Physics

4) High Power Input Couplers for Injector I &II



- Three kinds of couplers have been designed, fabricated and tested for different types of ADS cavities.

The main parameters of ADS power couplers

Cavity	Frequency (MHz)	Power (kW)	Q _{ext}	Connecting type
SPOKE	325	10,CW,TW	~7.0E5	Coaxial waveguide, $3\frac{1}{8}$ " ,50Ω
HWR	162.5	15,CW,TW	~7.0E5	Coaxial waveguide, YX50-105-1
RFQ	325 &162.5	80,CW,TW	~5670	WR2300



Under high power test;
Power level: 10 kW, CW,TW



Installed in the
Spoke012 Cavity



Operated with cavity;
Power level:10 kW, CW, SW



Next steps in the Energy Frontier-
Hadron Colliders



4. Key technology for SppC



- CSNS & C-ADS will be the solid basis of future SppC
 - Key tech:
 - **High field magnets:** both dipoles (20 T) and quadrupoles (pole tip field: 14-20 T) are technically challenging
 - **Beam screen and vacuum:** the key issue to solve the problem with very high synchrotron radiation power inside the cold vacuum. Need to develop an effective structure and working temperature to guide out the high heat load when minimizing Second-Electron-Yield, heat leakage to cold mass, impedance in the fast ramping field, vacuum instability etc.
 - **Collimation system:** requiring unprecedentedly high efficiency, may need some collimators in cold sections.
-

R&D plan of the 20 T accelerator magnets

(Very Preliminary)



- **2015-2020:** Development of a 12 T operational field Nb₃Sn twin-aperture dipole with common coil configuration and 10⁻⁴ field quality; Fabrication and test of 2~3 T HTS (Bi-2212 or YBCO) coils in a 12 T background field and basic research on tape superconductors for accelerator magnets (field quality, fabrication method, quench protection).
- **2020-2025:** Development of a 15 T Nb₃Sn twin-aperture dipole and quadrupole with 10⁻⁴ field uniformity; Fabrication and test of 4~5 T HTS (Bi-2212 or YBCO) coils in a 15 T background field.
- **2025-2030:** 15 T Nb₃Sn coils + HTS coils (or all-HTS) to realize the 20 T dipole and quadrupole with 10⁻⁴ field uniformity; Development of the prototype SppC dipoles and quadrupoles and infrastructure build-up.

20 T magnet working group in China

IHEP

CHMFL



newcomer



Superconducting magnetic separator (2012)

25Hz AC quadrupole for CSNS(2013)

11 T Nb₃Sn solenoid (ongoing)




BESIII Superconducting solenoid (2006)
08-26-14

Conventional magnets for BEPCII (2005)
Next steps in the Energy Frontier -
Hadron Colliders


11 T Nb₃Sn + 29 T Cu insert
(ongoing)

5. Summary



- **CEPC + SppC preliminary schedule:**
 - **CPEC**
 - Pre-study, R&D and preparation work
 - Pre-study: 2013-15 → Pre-CDR by 2014
 - R&D: 2016-2020
 - Engineering Design: 2015-2020
 - Construction: 2021-2027
 - Data taking: 2030-2036
 - **SPPC**
 - Pre-study, R&D and preparation work
 - Pre-study: 2013-2020
 - R&D: 2020-2030
 - Engineering Design: 2030-2035
 - Construction: 2036-2042
 - Data taking: 2042 -

Pre-CDR



- Writing up the preliminary Conceptual Design Report (pre-CDR), covering accelerator, theory, experiment (detector and physics), and civil engineering. → **1st milestone**

Schedule guideline for CEPC pre-CDR

August – December 2014

August 1-15	August 16-31	September 1-15	September 16-30	October 1-15	October 16-31	November 1-15	November 16-30	December 1-15	December 16-31
pre-CDR draft version 0 from each (sub-)group ; (with all required elements, some contents may be missing)									
(1) external reviewers identified and invitations sent out during first period; (2) additions and revisions being worked on; (3) formation of editorial board at SJTU workshop; (4) internal reviews within (sub-)groups.									
(1) revision and finalization of pre-CDR chapters; (2) internal reviews of chapters (theory, detector-simulation, accelerator, site design and civil engineering); (3) draft Introduction and Summary sections available for comments and revision.									
(1) reviews of chapters (theory, detector-simulation, accelerator, site design and civil engineering) by external review committees; (2) revisions of and improvements to the pre-CDR chapters .									
(1) final edition (including Introduction & Summary) in English; (2) translation of pre-CDR into Chinese completed and reviewed									
(1) proof; (2) print and release to CAS and public									

08-26-14

Next steps in the Energy Frontier -
Hadron Colliders

高能物理研究所
High Energy Physics

Pre-CDR: Accelerator




Table of Contents (Draft, February 10, 2014)

Executive summary


1. Introduction
2. Sciences of CEPC and SppC
3. Machine layout and performance
4. CEPC – accelerator physics
 - 1) Main parameters
 - 2) Lattice
 - 3) Interaction region and machine-detector interface
 - 4) Beam instability
 - 5) Beam-beam effects
 - 6) Synchrotron radiation
 - 7) Injection and beam dump
 - 8) Background
 - 9) Polarization
5. CEPC – technical systems
 - 1) Superconducting RF system
 - 2) Cryogenic system
 - 3) Magnets
 - 4) Vacuum
 - 5) Power supplies
 - 6) Instrumentation
 - 7) Control system
 - 8) Radiation shielding
 - 9) Survey and alignment
6. CEPC – injectors
 - 1) e+ and e- sources
 - 2) Linac
 - 3) Booster ring
7. Upgrade to SppC
 - 1) Key accelerator physics issues
 - i. Main parameters
 - ii. Synchrotron radiation
 - iii. Beam-beam effects
 - iv. Electron cloud effect
 - 2) Key technical systems
 - i. High field superconducting magnet
 - ii. Vacuum and beam screen
 - 3) Reconfiguration of the accelerator complex
8. Other possible upgrades
 - 1) ep
 - 2) $\gamma\gamma$
9. Civil construction
10. Environment, safety and health considerations
11. R&D programs
12. Project plan and cost estimate

**Most chapters ready
for internal review**

**Theory/Detector &
Physics chapters in
similar status**



-
- High energy accelerators are being developed in China for 30 years.
 - CEPC + SppC is the key direction for HEP, and big (HEP) accelerator as well in China.
 - We are rather weak in hadron machine, with CSNS and ADS projects just started.
 - R&D of key technologies are necessary and crucial to us.
 - More international collaboration is foreseen.
-



Thanks for your attention !